



**1/2" Flexible 4.3-10 Male Right Angle to 4.3-10 Male Right Angle Low PIM Jumper**  
**|123-1HMRHMR |123e.com**  
Part Number: 123-1HMRHMR-XX-P

4.3-10 Male Right Angle to 4.3-10 Male Right Angle welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

#### CROSS REFERENCE

Alternative To

#### PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male Right Angle
Connector B	4.3-10 Male Right Angle
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

#### ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.