

**1/2" Flexible 4.3-10 Male to 4.3-10 Male Low PIM Jumper |123-1HMHM |123e.com**
Part Number: 123-1HMHM-XX-P

4.3-10 Male to 4.3-10 Male welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To	LDF4-50, L4-HMHM-1M-D
----------------	-----------------------

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

PHYSICAL SPECIFICATIONS

Maximum Bending Radius	2.00"
Connector A	4.3-10 Male
Connector B	4.3-10 Male
Jacket Color	Black
Jacket Material	PE - UV Resistant
Outer Diameter	.63in

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.