

1/2" Flexible 7/16 DIN Male to 7/16 DIN Male Low PIM Jumper |123-1DMDM|123e.com
Part Number: 123-1DMDM-XX-P



7/16 DIN Male to 7/16 DIN Male Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. Made in the USA.

CROSS REFERENCE

Alternative To 7M7ML12-060FFP, 815396-906, L4A-DMDM-3m-P, SLJ12RP-60M60M-3m, L4A-PDMDM-3M

PHYSICAL SPECIFICATIONS

Connector A	7/16 DIN Male
Connector B	7/16 DIN Male
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.