



30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com



## 1/2" Flexible Mini Din 4.1/9.5 Male to Mini Din 4.1/9.5 Male Low PIM Jumper |123-1MDMMDM|123e.com

Part Number: 123-1MDMMDM-XX-P

1/2" Flexible Mini Din 4.1/9.5 Male to Mini Din 4.1/9.5 Male Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. Made in the USA.

|                              | 3                  |
|------------------------------|--------------------|
| CROSS REFERENCE              |                    |
| Alternative To               | L4A-KMKM-6-P-SGW   |
| ELECTRICAL SPECIFICATIONS    |                    |
| Frequency Range              | 600-3000 Mhz       |
| Impedance                    | 50 Ohm             |
| PIM                          | -165 dBc IEC 62037 |
| Return Loss                  | -30 db             |
| ENVIRONMENTAL SPECIFICATIONS |                    |
| Operating Temperature        | -40°C to +85°C     |
| Weather Standard             | IEC 68 40/85/ 21   |
| PHYSICAL SPECIFICATIONS      |                    |
| Maximum Bending Radius       | 2.00"              |
| Connector A                  | 4.1/9.5 Din Male   |
| Connector B                  | 4.1/9.5 Din Male   |
| Jacket Color                 | Black              |
| Jacket Material              | PE - UV Resistant  |
| Outer Diameter               | .63in              |
|                              |                    |