

**1/2" SuperFlex 7/16 DIN Male to 7/16 DIN Male Right Angle Low PIM Jumper**
|123-2DMDMR| 123e.com
Part Number: 123-2DMDMR-XX-P

7/16 DIN Male to 7/16 DIN Male Right Angle Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To	F4A-DMDR-3M-P
----------------	---------------

PHYSICAL SPECIFICATIONS

Dielectric Material	Foam PE
Connector A	7/16 DIN Male
Connector B	7/16 DIN Male Right Angle
Outer Diameter	<0.53in
Outer Conductor	Helically corrugated copper
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-171 dBc IEC 62037-2
Return Loss	-26dB @3GHz; -23dB @6GHz
VSWR	<1.10

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-55°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.