



1/4" Super Flex 4.3-10 Male to 2.25 Male Low PIM jumper w/EasyBoot on 4.3-10 side | 123-14SFHMJM-XX-P-EB1 | 123e.com

Part Number: 123-14SFHMJM-XX-P-EB1

4.3-10 Male to 2.25 Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This assembly has the EasyBoot weather boot installed on the 4.3-10 male connector end. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male w/EasyBoot
Connector B	2.25 Male
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-178 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.