



**1/4" Super Flex 4.3-10 Male to NEX10 Male Low PIM jumper | 123-14SFHMXM | 123e.com**  
Part Number: 123-14SFHMXM-XX-P



NEX10™ Male to 4.3-10 Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

#### CROSS REFERENCE

Alternative To	F1A-HMXM-3
----------------	------------

#### PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male
Connector B	Nex10 Male
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

#### ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-178 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.