



30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com



1/4" Super Flex 7/16" Male to 7/16" Male Low PIM jumper | 123-14SFDMDM |123e.com Part Number: 123-14SFDMDM-XX-P

7/16" DIN Male to 7/16" DIN Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

	· · · · · · · · · · · · · · · · · · ·
CROSS REFERENCE	
Alternative To	F1A-DMDM
ELECTRICAL SPECIFICATIONS	
Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-168 dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21
PHYSICAL SPECIFICATIONS	
Maximum Bending Radius	0.78"
Connector A	7/16" DIN Male
Connector B	7/16" DIN Male
Jacket Color	Black
Jacket Material	PE - UV Resistant
Outer Diameter	0.252in