



## 1/4" Super Flex N Male Right Angle to SMA Male Low PIM jumper | 123-14SFNMRSMA| 123e.com

Part Number: 123-14SFNMRSMA-XX-P

N Male Right Angle to SMA Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

|                        |                    |
|------------------------|--------------------|
| Connector A            | N Male Right Angle |
| Connector B            | SMA Male           |
| Outer Diameter         | 0.252in            |
| Jacket Color           | Black              |
| Jacket Material        | PE - UV Resistant  |
| Maximum Bending Radius | 0.78"              |

### ELECTRICAL SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz               |
| Impedance       | 50 Ohm                     |
| PIM             | -165 dBc                   |
| Return Loss     | ≤-27dB @3GHz, ≤-25dB @6GHz |

### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.