



**1/2" Flexible 4.3-10 Male Right Angle to 4.3-10 Male Right Angle Low PIM Jumper**  
**|123-1HMRHMR |123e.com**  
Part Number: 123-1HMRHMR-XX-P

4.3-10 Male Right Angle to 4.3-10 Male Right Angle welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

#### CROSS REFERENCE

Alternative To

#### PHYSICAL SPECIFICATIONS

|                        |                         |
|------------------------|-------------------------|
| Connector A            | 4.3-10 Male Right Angle |
| Connector B            | 4.3-10 Male Right Angle |
| Outer Diameter         | .63in                   |
| Jacket Color           | Black                   |
| Jacket Material        | PE - UV Resistant       |
| Maximum Bending Radius | 2.00"                   |

#### ELECTRICAL SPECIFICATIONS

|                 |                    |
|-----------------|--------------------|
| Frequency Range | 600-3000 Mhz       |
| Impedance       | 50 Ohm             |
| PIM             | -165 dBc IEC 62037 |
| Return Loss     | -30 db             |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.