



**1/2" Flexible (LDF4-50A) 7/16 DIN Male Right Angle to N Male Low PIM Jumper |**  
**123-1DMRNM |123e.com**  
Part Number: 123-1DMRNM-XX-P

7/16 DIN Male Right Angle to N Male Low PIM factory made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. Made in the USA.

#### CROSS REFERENCE

|                |                |
|----------------|----------------|
| Alternative To | L4A-PNMDR-20-I |
|----------------|----------------|

#### PHYSICAL SPECIFICATIONS

|                        |                           |
|------------------------|---------------------------|
| Connector A            | 7/16 DIN Male Right Angle |
| Connector B            | N Male                    |
| Outer Diameter         | .63in                     |
| Jacket Color           | Black                     |
| Jacket Material        | PE - UV Resistant         |
| Maximum Bending Radius | 2.00"                     |

#### ELECTRICAL SPECIFICATIONS

|                 |                    |
|-----------------|--------------------|
| Frequency Range | 600-3000 Mhz       |
| Impedance       | 50 Ohm             |
| PIM             | -165 dBc IEC 62037 |
| Return Loss     | -30 db             |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.