



## 1/2" Flexible 7/16 DIN Male to 7/16 DIN Male Low PIM Jumper |123-1DMDM|123e.com

Part Number: 123-1DMDM-XX-P

7/16 DIN Male to 7/16 DIN Male Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. Made in the USA.

### CROSS REFERENCE

Alternative To 7M7ML12-060FFP, 815396-906, L4A-DMDM-3m-P, SLJ12RP-60M60M-3m, L4A-PDMDM-3M

### PHYSICAL SPECIFICATIONS

|                        |                   |
|------------------------|-------------------|
| Connector A            | 7/16 DIN Male     |
| Connector B            | 7/16 DIN Male     |
| Outer Diameter         | .63in             |
| Jacket Color           | Black             |
| Jacket Material        | PE - UV Resistant |
| Maximum Bending Radius | 2.00"             |

### ELECTRICAL SPECIFICATIONS

|                 |                    |
|-----------------|--------------------|
| Frequency Range | 600-3000 Mhz       |
| Impedance       | 50 Ohm             |
| PIM             | -165 dBc IEC 62037 |
| Return Loss     | -30 db             |

### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C   |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.