

1/2" Flexible 4.3-10 Male to NEX10 Male Low PIM jumper w/EasyBoot on 4.3-10|
123-1HMXM-XX-P-EB1 | 123e.com
Part Number: 123-1HMXM-XX-P-EB1



4.3-10 Male to Nex10 Male welded onto 1/2 inch Flexible Rated Coaxial Cable, with an EasyBoot weather proofing boot on the 4.3-10 Male connector. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male Easy Boot
Connector B	NEX10 Male
Outer Diameter	0.307in (7.8mm)
Inner Conductor	Copper clad aluminum wire
Outer Conductor	Helical corrugated copper
Jacket Color	Black
Insulation	PE Spline
Jacket Material	PE - UV Resistant
Maximum Bending Radius	1.18"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50±2 Ohm
PIM	-156dBc
Return Loss	≤-30dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +80°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.