



1/4" Super Flex 7/16" Male RA to NEX10 Male Low PIM jumper | 123-14SFDMRXM |123e.com

Part Number: 123-14SFDMRXM-XX-P

7/16" DIN Male Right Angle to NEX10™ Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

| | |
|----------------|-----------|
| Alternative To | F1A-DMRXM |
|----------------|-----------|

PHYSICAL SPECIFICATIONS

| | |
|------------------------|----------------------------|
| Connector A | 7/16" DIN Male Right Angle |
| Connector B | Nex10 Male |
| Outer Diameter | 0.252in |
| Jacket Color | Black |
| Jacket Material | PE - UV Resistant |
| Maximum Bending Radius | 0.78" |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz |
| Impedance | 50 Ohm |
| PIM | -165 dBc |
| Return Loss | ≤-27dB @3GHz, ≤-24dB @6GHz |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.