

**1/4" Superflexible Plenum 7/16 DIN Male to 2.2-5 Male Low PIM jumper | 123-14SFPDMJM | 123e.com**

Part Number: 123-14SFPDMJM-XX-P

7/16 DIN Male to 2.2-5 Male welded onto 1/4 inch SuperFlexible Plenum Rated Coaxial Cable, white FR-PVC jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To SPP250DM25M

PHYSICAL SPECIFICATIONS

Connector A 7/16 DIN Male

Connector B 2.2-5 Male

Outer Diameter 0.307in (7.8mm)

Inner Conductor Copper clad aluminum wire

Outer Conductor Helical corrugated copper

Jacket Color White

Insulation PE Spline

Jacket Material halogenated fire retardant white jacket to meet UL CATVP/CMP rating.

Maximum Bending Radius 1.18"

ELECTRICAL SPECIFICATIONS

Frequency Range 600-3000 Mhz

Impedance 50 ± 2 Ohm

PIM -168 dBc

Return Loss $\leq -30\text{dB}$ @3GHz, $\leq -24\text{dB}$ @6GHz**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature -20°C to +80°C

Weather Standard IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.