123eWireless
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

1/4" Superflexible Plenum 4.3/10 Male to QMA Male Low PIM jumper | 123-14SFPHMQMA | 123e.com
Part Number: 123-14SFPHMQMA-XX-P

4.3/10 Male to QMA Male welded onto 1/4 inch SuperFlexible Plenum Rated Coaxial Cable, white FR-PVC jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE	
Alternative To	SPP25043MQM3.0F
PHYSICAL SPECIFICATIONS	
Connector A	4.3/10 Male
Connector B	QMA Male
Outer Diameter	0.307in (7.8mm)
Inner Conductor	Copper clad aluminum wire
Outer Conductor	Helical corrugated copper
Jacket Color	White
Insulation	PE Spline
Jacket Material	halogenated fire retardant white jacket to meet UL CATVP/CMP rating.
Maximum Bending Radius	1.18"
ELECTRICAL SPECIFICATIONS	
Frequency Range	600-3000 Mhz
Impedance	50±2 Ohm
PIM	-156dBc
Return Loss	≤-30dB @3GHz, ≤-24dB @6GHz
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-20°C to +80°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.