

**2.2-5 Male to SMA Male Low Loss Fire Rated 240 | 123-14JMSMA-XX-FR | 123e.com**  
Part Number: 123-14JMSMA-XX-FR



2.2-5 Male to SMA Male LMR type low loss 240 with a fire rated jacket. This high-performance RF coaxial cable assembly is engineered for reliable, low-loss signal transmission in demanding applications. It features a fire-retardant outer jacket that meets stringent safety standards, making it ideal for environments where fire protection is critical. Designed with excellent flexibility and enhanced durability, this assembly delivers long-term performance and dependable operation in challenging installations.

**CROSS REFERENCE**

Alternative To

**PHYSICAL SPECIFICATIONS**

Connector A	2.2-5 Male
Connector B	SMA Male
Coax Cable Type	Low Loss 240, Fire Rated
Outer Diameter	6.10 ± 0.10 mm
Jacket Color	Black
Jacket Material	LSZH-FRPE

**ELECTRICAL SPECIFICATIONS**

Frequency Range	Cut Off frequency = 31.00 GHz
Impedance	50 Ohm
Return Loss	-18db

**ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature	-40°C To +85°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.