



LC/UPC-Optitap (SC/APC) 2F Duplex, Single Mode | 123-F1D2-1A4H7 | 123e.com
Part Number: 123-F1D2-1A4H7

2 Fiber, Singlemode, LC/UPC- DUAL Optitap (SC/APC), I/O Riser. Compatible with Corning's Optisheath® multiport terminals. Designed for Ericsson 2203, 2205, and RRUS radios, available in ArmorFlex. OptiTap® is a registered trademark of Corning.

CROSS REFERENCE

Alternative To ANDFHBDW-H2Q22, DX OptiTap/LC, FHBDW-H2Q22

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	Optitap (SC/APC) Duplex
Fiber Count	2
Breakout Length Side A	6IN
Breakout Length Side B	12IN
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.