



**PUSHLOK(TM) OPTAP CONVERTER / LC UPC CONNECTOR, DUPLEX, CLEARCURVE(R) LBL,  
2F SST-DROP(R), DIELECTRIC | 123-D30402JB4FDXXXF-P | 123e.com**

Part Number: 123-D30402JB4FDXXXF-P

**Evolv® SST-Drop™ with Pushlok® Technology 2F Pushlok to LC Duplex, Dielectric**

This versatile cable is engineered for aerial, direct burial, and conduit installations, making it ideal for for outside plant (OSP) FTTx access networks. Compatible with Corning's Evolv® Optical Tap Terminals, it offers fully sealed environmental protection and quick, hassle-free connections. Designed to save space and speed up installations. This assembly directly compares to Corning D30402JB4FD035F-P.

\*All trademarks mentioned are the property of their respective owners.

#### CROSS REFERENCE

Alternative To D30402JB4FD035F-P, D30402JB4FD050F-P, D30402JB4FD075F-P

#### PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	Evolv Pushlok (SC/APC)
Fiber Count	2
Breakout Length Side A	6IN
Breakout Length Side B	53IN ± 1IN
Outer Diameter	
Fiber Type	SMF-28E
Jacket Color	Black
Jacket Material	SST Drop

#### ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

#### OPTICAL SPECIFICATIONS

Insertion Loss	Bi Dir. 1310nm, 1550nm, < 0.5 dB
Return Loss	>50 dB

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.