



PUSHLOK(TM) OPTAP CONVERTER / LC UPC CONNECTOR, DUPLEX, CLEARCURVE(R) LBL, 2F SST-DROP(R), DIELECTRIC | 123-D30402JB4FDXXXF-P | 123e.com
Part Number: 123-D30402JB4FDXXXF-P

Evolv® SST-Drop™ with Pushlok® Technology 2F Pushlok to LC Duplex, Dielectric

This versatile cable is engineered for aerial, direct burial, and conduit installations, making it ideal for for outside plant (OSP) FTTx access networks. Compatible with Corning's Evolv® Optical Tap Terminals, it offers fully sealed environmental protection and quick, hassle-free connections. Designed to save space and speed up installations. This assembly directly compares to Corning D30402JB4FD035F-P.

*All trademarks mentioned are the property of their respective owners.

CROSS REFERENCE

Alternative To D30402JB4FD035F-P, D30402JB4FD050F-P, D30402JB4FD075F-P

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	Evolv Pushlok (SC/APC)
Fiber Count	2
Breakout Length Side A	6IN
Breakout Length Side B	53IN ± 1IN
Outer Diameter	
Fiber Type	SMF-28E
Jacket Color	Black
Jacket Material	SST Drop

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	Bi Dir. 1310nm, 1550nm, < 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.