**123eWireless**
30412 Esperanza, Rancho Santa Margarita
CA 92688, (888) 263-6000
sales@123ewireless.com

**3/8" Super Flex 7/16 Din Male to NEX10 Male with EasyBoot Low PIM Jumper |123-38SFDMXM-XX-P-EB2 |123e.com**
Part Number: 123-38SFDMXM-XX-P-EB2

7/16 Din Male to NEX10 Male with EasyBoot welded onto 3/8" Super Flex cable, Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

| | |
|---|---|
| **CROSS REFERENCE** | |
| Alternative To | |
| **PHYSICAL SPECIFICATIONS** | |
| Connector A | 7/16 Din Male |
| Connector B | NEX10 Male with EasyBoot weather protection |
| Inner Conductor | Copper-Clad Aluminum 1.90mm (0.075in) |
| Outer Conductor | Helically Corrugated Copper 6.40mm (0.252in) |
| Jacket Color | Black |
| Insulation | Physically Foamed PE 4.70mm (0.185in) |
| Jacket Material | PE - UV Resistant |
| Maximum Bending Radius | 2.00" |
| **ELECTRICAL SPECIFICATIONS** | |
| Frequency Range | Max 10.2 GHz |
| Impedance | 50±2 Ohm |
| Peak Power | 13.2 kW |
| PIM | -165 dBc IEC 62037 |
| Return Loss | -30 db |
| **ENVIRONMENTAL SPECIFICATIONS** | |
| Operating Temperature | -55°C to +85°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.
Please contact us at sales@123ewireless.com for any queries.