



**4.3-10 Male to 4.3-10 Female 20dB 50 Watts Attenuator | 123-H20dB50W | 123e.com**  
Part Number: 123-H20dB50W

50W DC-6GHz 20dB 4.3-10-male to 4.3-10-female RF attenuator. Fixed attenuators are used to lower voltage, dissipate power, and to improve impedance matching.

- ◆ Wide Frequency Band DC-6GHz
- ◆ 2G/6G/4G/LTE Coverage
- ◆ Low VSWR
- ◆ Widely used for In-building Solutions

## CROSS REFERENCE

Alternative To

## PHYSICAL SPECIFICATIONS

|             |               |
|-------------|---------------|
| Connector A | 4.3/10 Male   |
| Connector B | 4.3/10 Female |

## ELECTRICAL SPECIFICATIONS

|                 |                |
|-----------------|----------------|
| Attenuation     | 20dB $\pm$ 1.1 |
| Average Power   | 50 W           |
| Frequency Range | DC-6GHz        |
| Impedance       | 50 ohm         |
| VSWR            | $\leq$ 1.25    |

## ENVIRONMENTAL SPECIFICATIONS

|                       |            |
|-----------------------|------------|
| Operating Temperature | -30C ~+65C |
|-----------------------|------------|

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.