



**4.3-10 Male 40 Watt RF Load Terminator, Low PIM | 123-HMT40-P | 123e.com**  
Part Number: 123-HMT40-P

40W Low PIM Termination Load (600-6000MHz, -160dBc, 4.3/10-male) also known as a dummy load.

- Wide Frequency Band 600-6000MHz
- 2G/3G/4G/LTE Coverage
- Low VSWR
- Low Passive Intermodulation -160dBc
- Widely used for Indoor Solutions

## CROSS REFERENCE

Alternative To

## PHYSICAL SPECIFICATIONS

|             |             |
|-------------|-------------|
| Weight      | 0.55 (kg)   |
| Connector A | 4.3/10 Male |
| Gender      | Male        |

## ELECTRICAL SPECIFICATIONS

|                 |                                                                                |
|-----------------|--------------------------------------------------------------------------------|
| Average Power   | 40 Watts                                                                       |
| Frequency Range | 600-6000MHz                                                                    |
| Impedance       | 50 ohm                                                                         |
| PIM             | $\leq -160\text{dBc}@2*43\text{dBm}$                                           |
| VSWR            | $600\text{--}3800\text{MHz} \leq 1.30$ $3800\text{--}6000\text{MHz} \leq 1.35$ |

## ENVIRONMENTAL SPECIFICATIONS

|                       |                                                |
|-----------------------|------------------------------------------------|
| Operating Temperature | $-30^{\circ}\text{C} \sim +65^{\circ}\text{C}$ |
|-----------------------|------------------------------------------------|

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.