



Armored LC Uniboot w/short boot overmold to LC Uniboot Duplex, Singlemode 4F Distribution | 123-F4X4-1A4DD-XX-OM1-001 | 123e.com
Part Number: 123-F4X4-1A4DD-XX-OM1-001

Armored LC Uniboot w/short boot overmold to LC Uniboot Duplex, Singlemode 4F Distribution

CROSS REFERENCE

Alternative To	FJ-4SM-008-5M
----------------	---------------

PHYSICAL SPECIFICATIONS

Connector A	LC Uniboot w/short boot overmold
Connector B	LC Uniboot Duplex
Fiber Count	4
Breakout Length Side A	28 Inches
Breakout Length Side B	10 Inches
Furcation	3 mm
Outer Diameter	5.2mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	Armored

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.