

LC/UPC-SC/UPC 4F Simplex, Single Mode I/O Riser with a Pulling Sock | 123-F3X4-1A436-XX-PS | 123e.com

Part Number: 123-F3X4-1A436-XX-PS



LC/UPC to SC/UPC Simplex, Singlemode 4 fiber round distribution indoor/outdoor jumper with a pulling sock for easy installation.

CROSS REFERENCE

Alternative To FB-L98B-A1151-050FT, FB-L98B-A1151-125FT, FB-L98B-A1151

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Simplex
Connector B	SC/UPC Simplex w/Pulling Sock
Fiber Count	4
Breakout Length Side A	6 Inches
Breakout Length Side B	6 Inches
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.