



**4.1/9.5 Mini DIN male solder center solder body connector for 1/2" Standard Flexible Cable | 123-1MDMS | 123e.com**  
Part Number: 123-1MDMS

4.1/9.5 Mini DIN male solder center solder body connector for 1/2" regular flexible annular cable 123-1-50 or equivalent. This connector is factory installed onto any other manufacturers 1/2" flexible cable including Commscope LDF4-50, and RFS LCF12-50J-P7.

**Installation Method:**

- **Center Pin:** Solder attachment
- **Body Connection:** Solder attachment

**Impedance:**

50 Ohms

**Frequency Range:**

Supports high-frequency signals with precision and minimal attenuation

**Applications:**

- RF communication systems
- Cellular base stations
- Antenna connections
- High-frequency testing setups

## CROSS REFERENCE

Alternative To

## ELECTRICAL SPECIFICATIONS

Frequency Range	DC-3GHz
Impedance	50 Ohms
PIM	< -160 dBc
VSWR	< 1.15

## ENVIRONMENTAL SPECIFICATIONS

Weather Standard	IP68
------------------	------

## PHYSICAL SPECIFICATIONS

Gender	Male
Inner Conductor	Brass, Silver Plated
Insulation	PTFE
Options	Solder Type
Outer Conductor	Brass, CuSnZn Plated
Connector A	4.1/9.5 Din

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.