



4.3/10 Female to 4.3/10 Male Attenuator, 20dB 20 Watt | 123-H20dB20W | 123e.com

Part Number: 123-H20dB20W

20W, 20dB RF Attenuator (DC-6GHz, 4.3/10-Male to 4.3/10-Female)

This high-performance RF attenuator is designed for superior signal management across a wide frequency band of DC to 6 GHz. Its key features include:

- **Wide Frequency Range:** Supports DC to 6 GHz for versatile applications.
- **Multi-Technology Compatibility:** Ideal for 2G, 3G, 4G, and LTE networks.
- **Low VSWR:** Ensures minimal signal reflection for optimal performance.
- **Broad Application Use:** Perfect for in-building solutions and other RF systems.

Durable and reliable, this attenuator is equipped with a 4.3/10-male to 4.3/10-female interface for seamless integration. It's an essential component for fine-tuning signal levels in telecommunications and network installations.

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male
Connector B	4.3-10 Female

ELECTRICAL SPECIFICATIONS

Attenuation	20dB \pm 1.0
Average Power	20 Watts @ 25°C
Frequency Range	DC-6GHz
Impedance	50 ohm
VSWR	\leq 1.25

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-30C~+65C
-----------------------	-----------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.