



**4.3-10 Male to N Male RG401 (Flex Form 0.27") | 123-14FFHMNM | 123e.com**  
Part Number: 123-14FFHMNM-XX-P

4.3-10 Male to N Male 1/4 inch FlexForm™ Low PIM factory made jumper

#### CROSS REFERENCE

|                |                |
|----------------|----------------|
| Alternative To | TFT-401, RG401 |
|----------------|----------------|

#### PHYSICAL SPECIFICATIONS

|                 |                         |
|-----------------|-------------------------|
| Connector A     | 4.3-10 Male             |
| Connector B     | N Male                  |
| Outer Diameter  | 7.00±0.15 mm            |
| Inner Conductor | Silver-coated Copper    |
| Outer Conductor | Tin Soaked Copper Braid |
| Jacket Color    | White                   |
| Insulation      | Solid PTFE              |

#### ELECTRICAL SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Frequency Range | up to 18Ghz                |
| Impedance       | 50 Ohm                     |
| PIM             | -164dBc                    |
| Return Loss     | ≤-27dB @3GHz, ≤-24dB @6GHz |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -55°C to +125°C  |
| RoHS Compliance       | Yes              |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.