



48F Trunk, 24 Duplex LC Uniboot - 24 Duplex LC Uniboot, SM 9/125, 250um | 123-F3X48-1A5DD-XX-PS | 123e.com

Part Number: 123-F3X48-1A5DD-XX-PS

48 FIBER TRUNK, 24 Duplex LC Uniboot to 24 Duplex LC Uniboot , CABLE SM, 48 FIBERS 9/125 ,250um, 24" Fanout Both sides. A pulling sock is added for convenience.

CROSS REFERENCE

Alternative To	RFFT-48SM-00
----------------	--------------

PHYSICAL SPECIFICATIONS

Connector A	24 Duplex LC Uniboot
Connector B	24 Duplex LC Uniboot
Fiber Count	48
Breakout Length Side A	24" Fanout
Breakout Length Side B	24" Fanout
Furcation	3 mm
Outer Diameter	8.5 mm ±0.2
Fiber Type	SMF-28 Ultra
Jacket Color	Black
Jacket Material	Flame Retardant PVC

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.