



**5G LC/HD PPT - LC/HD PPT 1F Simplex, Single Mode I/O Riser | 123-F1S1-1A4QQ | 123e.com**

Part Number: 123-F1S1-1A4QQ

1 Fiber, Singlemode, LC/HD PPT to LC/HD PPT, I/O Riser. The LC/HD PPT is made to fit into the JONHON connector and Samsung Radio, available in ArmorFlex. OptiTap® is a registered trademark of Corning.

## CROSS REFERENCE

Alternative To

## PHYSICAL SPECIFICATIONS

Connector A	LC/HD PPT
Connector B	LC/HD PPT
Fiber Count	1
Breakout Length Side A	N/A
Breakout Length Side B	N/A
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

## ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
-----------------------	----------------

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.