

6 Fiber Single mode, LC/UPC to SC/UPC, I/O Rated, W/Pulling Sock both sides | 123-F3X6-1A427-XX-PS | 123e.com

Part Number: 123-F3X6-1A427-XX-PS



LC/UPC to SC/UPC, Singlemode 6 fiber round distribution indoor/outdoor jumper with a pulling sock on each end for easy installation.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC with pulling sock
Connector B	SC/UPC w/Pulling Sock
Fiber Count	6
Breakout Length Side A	18 Inches
Breakout Length Side B	24 Inches
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.