



LC/UPC Duplex to Optitap (SC/APC) 6 Fiber Aerial Distri, with puling sock and custom Breakout| 123-F3X6-8A4H7-XX-PS | 123e.com

Part Number: 123-F3X6-8A4H7-XX-PS

LC/UPC Duplex to Optitap (SC/APC) 6 Fiber Aerial Distribution cable, with puling sock and custom breakouts.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	Optitap (SC/APC)
Connector B	LC/UPC with heavy duty pulling sock
Fiber Count	6
Breakout Length Side A	10FT/6FT/4FT
Breakout Length Side B	250FT/15FT
Outer Diameter	7.7mm with a 1/4" Galvanized Strength Member and 5.4mm breakout cable
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -20°C to +70°C

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.