



**7/16 Din Male to 7/16 Din Male RG401 (Flex Form 0.27") | 123-14FFDMDM | 123e.com**  
Part Number: 123-14FFDMDM-XX-P

DIN (7/16) Male to DIN (7/16) Male 1/4 inch FlexForm™ Low PIM factory made jumper

#### CROSS REFERENCE

Alternative To CXTM02M-3-I

#### PHYSICAL SPECIFICATIONS

Connector A	7/16 Din Male
Connector B	7/16 Din Male
Outer Diameter	7.00±0.15 mm
Inner Conductor	Silver-coated Copper
Outer Conductor	Tin Soaked Copper Braid
Jacket Color	White
Insulation	Solid PTFE

#### ELECTRICAL SPECIFICATIONS

Frequency Range	up to 18Ghz
Impedance	50 Ohm
PIM	-162dBc
Return Loss	≤-27dB @3GHz, ≤-24dB @6GHz

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-55°C to +125°C
RoHS Compliance	Yes
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.