



**7/16 Din Male to 7/16 Din Male RG402 Plenum (Flex Form Mini .141) | 123-402DMDM | 123e.com**

Part Number: 123402DMDM-XX-P

7/16 Din Male to 7/16 Din Male RG402 Plenum (Flex Form Mini .141)

## CROSS REFERENCE

|                |         |
|----------------|---------|
| Alternative To | TFT-402 |
|----------------|---------|

## PHYSICAL SPECIFICATIONS

|                |              |
|----------------|--------------|
| Connector A    | 7/16 Male    |
| Connector B    | 7/16 Male    |
| Outer Diameter | 4.15±0.10 mm |
| Jacket Color   | Blue         |

## ELECTRICAL SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz               |
| Impedance       | 50 Ohm                     |
| PIM             | -162dBc                    |
| Return Loss     | ≤-27dB @3GHz, ≤-24dB @6GHz |
| VSWR            | ≤1.1@0~3G, ≤1.15@3~6G      |

## ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | -55°C to +125°C  |
| RoHS Compliance       | Yes              |
| Weather Standard      | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.