



**LC/UPC-LC/UPC 4F Simplex, Single Mode I/O Riser with a Pulling Sock | 123-F3X4-1A266-125F-PS-001 | 123e.com**

Part Number: 123-F3X4-1A266-XX-PS-001

LC/UPC to LC/UPC Simplex, Singlemode 4 fiber round distribution indoor/outdoor jumper with a pulling sock for easy installation. 6IN breakouts

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Simplex
Connector B	LC/UPC Simplex w/Pulling Sock
Fiber Count	4
Breakout Length Side A	6 Inches
Breakout Length Side B	6 Inches
Furcation	2 mm
Outer Diameter	5.4mm
Fiber Type	SMF-28® Ultra
Jacket Color	Black
Jacket Material	OFNR, I/O

### ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

### OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	None

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.