



Armored LC/UPC-LC/UPC 2F, Single Mode I/O LSZH | 123-F4X2-1A477-XX-PS-007 | 123e.com

Part Number: 123-F4X2-1A477-XX-PS-007

Armored LC/UPC-LC/UPC Indoor/Outdoor 5.0mm Armored LSZH SM 2 Fiber Round Distribution with 12IN breakout on side A and 4IN breakout on side B. A pulling sock is included for easy installation.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	LC/UPC Duplex
Fiber Count	2
Breakout Length Side A	12IN
Breakout Length Side B	4IN
Furcation	2 mm
Outer Diameter	5.0 mm ±0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	> 50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	1.0mm stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.