



Armored LC/UPC-LC/UPC with Heat Shrink 2F, Single Mode I/O Riser| 123-F4X2-1A4D7-XX-HS | 123e.com

Part Number: 123-F4X2-1A4D7-XX-HS

Armored LC/UPC uniboot with heat shrink to LC/UP duplex, Singlemode 2 fiber round distribution indoor/outdoor jumper. The heat shrink is added for extra strength and durability. Designed for Ericsson base station functionality for typical interconnection between RRU and BBU. CPRI, LTE, and 5G ready.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	LC/UPC Duplex
Connector B	LC/UPC Uniboot with heatshrink
Fiber Count	2
Breakout Length Side A	24IN
Breakout Length Side B	3IN of Heatshrink
Outer Diameter	5.0 mm $\pm$ 0.2
Fiber Type	G652D MM62.5/125 G657
Jacket Color	Black
Jacket Material	LSZH, I/O

ATTENUATION

Attenuation @ 1550nm	0.25 dB/km
Attenuation @ 1310nm	0.40 dB/km

OPTICAL SPECIFICATIONS

Insertion Loss	< 0.5 dB
Return Loss	>50 dB

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +70°C
Varmint Rating	Stainless steel armored tube

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.