

**1/2" Flexible 4.3-10 Male to N Female Low PIM Jumper | 123-1HMNF | 123e.com**
Part Number: 123-1HMNF-XX-P

4.3-10 Male to N Female welded onto 1/2" flexible cable, Low PIM, factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA. 4.3-10M to NF

CROSS REFERENCE

Alternative To	LDF4-50, L4-HMNF-1M-D
----------------	-----------------------

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male
Connector B	N Female
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.