

1/2" Flexible Plenum 7/16 Din Male to 4.3-10 Male With EasyBoot Low PIM jumper |
123-1PDMHM-XX-P-EB | 123e.com
Part Number: 123-1PDMHM-XX-P-EB

7/16 Din Male to 4.3-10 Male With EasyBoot welded onto 1/2 inch Flexible Plenum Rated Coaxial Cable, white PE jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	7/16 Din Male
Connector B	4.3-10 Male Easy Boot
Outer Diameter	0.627in (15.93mm)
Inner Conductor	Copper-Clad Aluminum 0.19in (4.8mm)
Outer Conductor	Annularly Corrugated Copper, 0.54in (13.8mm)
Jacket Color	White
Insulation	PE Spline
Jacket Material	Flexible Plenum, UL910 CMP, NEC 820-53(a) CATVP
Maximum Bending Radius	Single: 4.8in, (120mm); Repeated: 5.0in, (125mm)

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50±2 Ohm
PIM	-156dBc
Return Loss	≤-30dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +80°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.