



**N Male to SMA Right Angle Male LMR 240**  
Part Number: 123-14NMSMAR

N Male to SMA Right Angle Male LMR type low loss 240 assemblies RF jumpers are UL listed indoor/outdoor riser rated GPS unit Jumper

#### CROSS REFERENCE

|                |             |
|----------------|-------------|
| Alternative To | C240-NMNM-6 |
|----------------|-------------|

#### PHYSICAL SPECIFICATIONS

|                 |                      |
|-----------------|----------------------|
| Connector A     | N Male               |
| Connector B     | SMA Right Angle Male |
| Coax Cable Type | Low Loss 240         |
| Outer Diameter  | 0.24 (in)            |
| Jacket Color    | Black                |
| Jacket Material | PE - UV Resistant    |

#### ELECTRICAL SPECIFICATIONS

|                 |              |
|-----------------|--------------|
| Frequency Range | 698-2200 MHz |
| Impedance       | 50 Ohm       |
| Return Loss     | -18db        |

#### ENVIRONMENTAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Operating Temperature | -40°C To +85°C |
| Weather Standard      | IP 67          |

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.