



1/2" Flexible 4.3-10 Male with EasyBoot to 4.3-10 Male Right Angle Low PIM Jumper
|123-1HMHR-XX-P-EB1 |123e.com
Part Number: 123-1HMHR-XX-P-EB1

4.3-10 Male with EasyBoot weatherproofing boot to 4.3-10 Male Right Angle welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order intermodulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To L4-HMHR-8-SGW-D L4-HMHR-10-SGW-D L4-HMHR-12-SGW-D L4-HMHR-15-SGW-D

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Male with EasyBoot
Connector B	4.3-10 Male Right Angle
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.