



## 1/4" Super Flex N Male to N Male Right Angle Low PIM jumper | 123-14SFNMNMR | 123e.com

Part Number: 123-14SFNMNMR-XX-P

N Male to N Male Right Angle welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

### CROSS REFERENCE

Alternative To

### PHYSICAL SPECIFICATIONS

Connector A	N Male
Connector B	N Male Right Angle
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

### ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc
Return Loss	≤-27dB @3GHz, ≤-25dB @6GHz

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.