



1/4" Superflexible Plenum N Female to N Male Low PIM jumper | 123-14SFPNFM | 123e.com

Part Number: 123-14SFPNFM-XX-P

N Female to N Male welded onto 1/4 inch SuperFlexible Plenum Rated Coaxial Cable, white FR-PVC jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To SPP250NMNF3, PLA44-N1NF-W03

PHYSICAL SPECIFICATIONS

Connector A N Female

Connector B N Male

Outer Diameter 0.307in (7.8mm)

Inner Conductor Copper clad aluminum wire

Outer Conductor Helical corrugated copper

Jacket Color White

Insulation PE Spline

Jacket Material halogenated fire retardant white jacket to meet UL CATVP/CMP rating.

Maximum Bending Radius 1.18"

ELECTRICAL SPECIFICATIONS

Frequency Range 600-3000 Mhz

Impedance 50 ± 2 Ohm

PIM -156dBc

Return Loss ≤ -30 dB @3GHz, ≤ -24 dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -20°C to +80°C

Weather Standard IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.