



1/4" Superflexible Plenum QMA Male to QMA Male Low PIM jumper | 123-14SFPQMAQMA | 123e.com

Part Number: 123-14SFPQMAQMA-XX-P

QMA Male to QMA Male welded onto 1/4 inch SuperFlexible Plenum Rated Coaxial Cable, white FR-PVC jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To SPP250SQMQM

PHYSICAL SPECIFICATIONS

| | |
|------------------------|--|
| Connector A | QMA Male |
| Connector B | QMA Male |
| Outer Diameter | 0.307in (7.8mm) |
| Inner Conductor | Copper clad aluminum wire |
| Outer Conductor | Helical corrugated copper |
| Jacket Color | White |
| Insulation | PE Spline |
| Jacket Material | halogenated fire retardant white jacket to meet UL CATVP/CMP rating. |
| Maximum Bending Radius | 1.18" |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz |
| Impedance | 50±2 Ohm |
| PIM | -156dBc |
| Return Loss | ≤-30dB @3GHz, ≤-24dB @6GHz |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -20°C to +80°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.