



1/2in Flexible 4.3-10 Male to 4.3-10 Male Low PIM Jumper |123-1HMHM |123e.com
Part Number: 123-1HMHM-XX-P

4.3-10 Male to 4.3-10 Male welded onto 1/2" flexible cable, Low PIM factory made jumper. 123eWireless factory made assemblies are optimized to produce low passive third order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To LDF4-50, L4-HMHM-1M-D

PHYSICAL SPECIFICATIONS

| | |
|------------------------|-------------------|
| Connector A | 4.3-10 Male |
| Connector B | 4.3-10 Male |
| Outer Diameter | .63in |
| Jacket Color | Black |
| Jacket Material | PE - UV Resistant |
| Maximum Bending Radius | 2.00" |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|--------------------|
| Frequency Range | 600-3000 Mhz |
| Impedance | 50 Ohm |
| PIM | -165 dBc IEC 62037 |
| Return Loss | -30 db |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.