



1/2" SuperFlex N Male to N Male Low PIM Jumper |123-2NMNM| 123e.com
Part Number: 123-2NMNM-XX-P

N Male to N Male Low PIM factory-made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. MADE in the USA.

CROSS REFERENCE

Alternative To F4A-NMNM

PHYSICAL SPECIFICATIONS

| | |
|------------------------|-----------------------------|
| Dielectric Material | Foam PE |
| Connector A | N Male |
| Connector B | N Male |
| Outer Diameter | <0.53in |
| Outer Conductor | Helically corrugated copper |
| Jacket Color | Black |
| Jacket Material | PE - UV Resistant |
| Maximum Bending Radius | 2.00" |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|--------------------------|
| Frequency Range | 600-9200 Mhz |
| Impedance | 50 Ohm |
| PIM | -170 dBc IEC 62037-2 |
| Return Loss | -26dB @3GHz; -23dB @6GHz |
| VSWR | <1.10 |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -55°C to +85°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.