



1/4" Super Flex 4.3-10 Female to 4.3-10 Male Low PIM jumper with EasyBoots | 123-14SFHFHM-XX-P-EB | 123e.com

Part Number: 123-14SFHFHM-XX-P-EB

4.3-10 Female to 4.3-10 Male welded onto 1/4 inch Super Flexible jumper cable with EasyBoots, weather proofing boots. MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To F1A-HFHM, F1-HMHF

PHYSICAL SPECIFICATIONS

Connector A	4.3-10 Female with EasyBoot
Connector B	4.3-10 Male with EasyBoot
Outer Diameter	0.252in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	0.78"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-161dBc
Return Loss	≤-27dB @3GHz, ≤-25dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.