



1/4" Super Flex 4.3-10 Male to 4.3-10 Male Low PIM jumper | 123-14SFHMHM | 123e.com
Part Number: 123-14SFHMHM-XX-P

4.3-10 Male to 4.3-10 Male welded onto 1/4 inch Super Flexible jumper cable MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

| | |
|----------------|-------------|
| Alternative To | C240-HMNM-6 |
|----------------|-------------|

PHYSICAL SPECIFICATIONS

| | |
|------------------------|-------------------|
| Connector A | 4.3-10 Male |
| Connector B | 4.3-10 Male |
| Outer Diameter | 0.252in |
| Jacket Color | Black |
| Jacket Material | PE - UV Resistant |
| Maximum Bending Radius | 0.78" |

ELECTRICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Frequency Range | 600-3000 Mhz |
| Impedance | 50 Ohm |
| PIM | -178 dBc |
| Return Loss | ≤-27dB @3GHz, ≤-24dB @6GHz |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|------------------|
| Operating Temperature | -40°C to +85°C |
| Weather Standard | IEC 68 40/85/ 21 |

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.