



**1/2" Flexible (LDF4-50A) 7/16 DIN Male Right Angle to N Male Low PIM Jumper | 123-1DMRNM | 123e.com**  
Part Number: 123-1DMRNM-XX-P

7/16 DIN Male Right Angle to N Male Low PIM factory made jumper. 123eWireless factory-made assemblies are optimized to produce low passive third-order inter-modulation. Each jumper is dynamically PIM tested to IEC 62037 standards, certified to guarantee performance, and averages -165dBc. Made in the USA.

#### CROSS REFERENCE

Alternative To L4A-PNMDR-20-I

#### PHYSICAL SPECIFICATIONS

Connector A	7/16 DIN Male Right Angle
Connector B	N Male
Outer Diameter	.63in
Jacket Color	Black
Jacket Material	PE - UV Resistant
Maximum Bending Radius	2.00"

#### ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50 Ohm
PIM	-165 dBc IEC 62037
Return Loss	-30 db

#### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40°C to +85°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at [sales@123ewireless.com](mailto:sales@123ewireless.com) for any queries.