



**1/4" Superflexible Plenum SMA Male to NEX10 Male Low PIM jumper | 123-14SFPSMAXM
| 123e.com**

Part Number: 123-14SFPSMAXM-XX-P

SMA Male to NEX10 Male welded onto 1/4 inch SuperFlexible Plenum Rated Coaxial Cable, white FR-PVC jacket. This jumper cable is MADE IN THE USA. This small cell or DAS jumper is designed with few internal components which in turn reduces the inter-modulation distortion (IMD) averaging -165dBc. Each jumper is individually tested and certified to guarantee performance.

CROSS REFERENCE

Alternative To

PHYSICAL SPECIFICATIONS

Connector A	SMA Male
Connector B	NEX10 Male
Outer Diameter	0.307in (7.8mm)
Inner Conductor	Copper clad aluminum wire
Outer Conductor	Helical corrugated copper
Jacket Color	White
Insulation	PE Spline
Jacket Material	halogenated fire retardant white jacket to meet UL CATVP/CMP rating.
Maximum Bending Radius	1.18"

ELECTRICAL SPECIFICATIONS

Frequency Range	600-3000 Mhz
Impedance	50±2 Ohm
PIM	-156dBc
Return Loss	≤-30dB @3GHz, ≤-24dB @6GHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to +80°C
Weather Standard	IEC 68 40/85/ 21

Thank you visiting 123eWireless.

Please contact us at sales@123ewireless.com for any queries.